

# NO. 11 BW ROOFING GRANULES



## Commercial Product Data Sheet

### **Product Description**

Siplast No. 11 BW Roofing Granules are the same high quality mineral granules used on Siplast BW mineral-surfaced elastomeric asphalt products. No. 11 BW Roofing Granules are composed of a mineral specially treated for cool roof applications.

### **Product Uses**

No. 11 BW Roofing Granules should be used wherever hot mopping asphalt, PA-311 Adhesive, or SFT Adhesive extends onto the finished roof surface. No. 11 BW Roofing Granules should be applied while asphalt is hot or the Siplast adhesive is still "wet," and should be pressed into the asphalt surface to ensure proper adhesion.

*Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at [www.Siplast.com](http://www.Siplast.com).*

### **COMMERCIAL PRODUCT INFORMATION**

Unit: 5 Gallon Pail (19 liters)

Size: 3M - No. 11

100% - 8 Mesh Tyler (2.36 mm) Sieve  
95% + 35 Mesh Tyler (425) Sieve

Bulk Density: 60 - 80 lbs/ft<sup>3</sup> (963 - 1284 kg/m<sup>3</sup>)

Standard Color: Bright White

Packaging: The pails are stacked three high on pallets and stretched wrapped.

Pallet: 36 in X 48 in (91 cm X 122 cm) wooden pallet  
Number Pails Per Pallet: 36  
Number Pallets Per Truckload: 22  
Shipping Weight Per Pail: 50 lb (22.7 kg)

Storage and Handling: All containers of Siplast No. 11 Roofing Granules should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements.

Rev 5/2018