

PA-505 ASPHALT SPECIALTY PRIMER

Commercial Product Data Sheet

PA-505 Asphalt Specialty Primer is an asphalt solvent blend designed as a primer for pre-approved substrate prior to application of Siplast Roofing and Flashing Systems.

Contact Siplast for information on approved product uses.

USES: PRIMER

Standards	ASTM D41 Type II
Unit	5-gallon pail 4.7 gallons (18 liters) net content
Flash Point	>105°F (40.5°C)
Coverage	Typical coverage is 50 square feet per gallon (0.2 liters per m ²). Coverage is dependent on the condition of the surface receiving the primer.
VOC Content	>250 g/L

PRODUCT INFORMATION

Application

PA-505 Asphalt Specialty Primer is applied by roller or brush, and is recommended as a prime coat on surfaces approved in advance by Siplast prior to application of Siplast roof systems. When applied to a properly prepared substrate, PA-505 Asphalt Specialty Primer penetrates and cures to provide a smooth surface to receive torch-applied SBS modified bitumen membranes.



Storage and Handling

All containers of PA-505 Asphalt Specialty Primer should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat, fire or open flames.

Packaging

Pallet: 45 in X 48 in (114 cm X 122 cm) wooden pallet
 Pails Per Pallet: 42
 Weight Per Pail: 40 lb (18.14 kg)
 Pallets Per Truckload: 22