



PA-917 PRIMER

Commercial Product Data Sheet

PA-917 Primer is an asphalt solvent blend designed as a primer for metal, concrete and masonry surfaces prior to application of Siplast SBS Roofing and Flashing Systems.

Contact Siplast for information on approved product uses.

USES:
ASPHALT PRIMER

PRODUCT INFORMATION

Application

PA-917 Primer is applied to metal flanges, concrete and masonry surfaces prior to application of asphaltic sheet products. The primer should be allowed to dry thoroughly prior to application of Siplast SBS Roofing and Flashing Systems. PA-917 Primer can be applied by brush or roller. Do not dilute PA-917 Primer under any circumstances. Diluting PA-917 using petroleum solvents will affect bonding and drying characteristics.



Storage and Handling

All containers of PA-917 Primer should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat or open flames.

Packaging

Pallet: 45 in X 48 in (114 cm X 122 cm) wooden pallet
 Number Pails Per Pallet: 42
 Number Pallets Per Truckload: 22
 Weight Per Pail: 40 lb (18.1 kg)

Listings, Approvals, & Certifications



Standards	ASTM D41
Unit	5-gallon Pail 4.7 gallons (18 liters) net content
Flash Point	>71°F (21.6°C) ASTM D92 (Cleveland Open Cup)
Coverage	Coverage is dependent on the condition, profile and porosity of the surface receiving the primer. Typical coverage ranges from 100 square feet per gallon (0.4 liter per m ²) on very rough, porous surfaces to 300 square feet per gallon (1.2 liter per m ²) on smooth, low-absorptive surfaces.
VOC Content	<350 g/L