

PARABLOCK TAPE



Commercial Product Data Sheet

Product Description

Parablock Tape is used to secure the laps of Siplast Parablock Root Barrier. It is made from a cast polyethylene film coated with a high-tack synthetic elastomeric adhesive. The sealing tape resists moisture, cold temperature, and UV light.

Application Guidelines

Prior to installation of the Parablock Tape, wipe clean the lap area to be covered to ensure removal of all moisture, dirt, dust, or other contaminants that may otherwise inhibit full adhesion of the Parablock Tape. Remove release liner, center the width of the tape over the leading edge of the overlapping sheet and press the tape firmly, facilitating full contact between the tape adhesive and root barrier surface.

COMMERCIAL PRODUCT INFORMATION

Physical Properties

Unit: Roll
Thickness: 2 mils
Roll Width: 4 inches (101.6 mm)
Roll Length: 100 feet (30.49 m)
Roll Weight: 5.3 lb (2.4 kg)
Color: Black (Optional in Gray)

Mechanical Properties

Thickness: 25 ± 2 mils
Tensile Strength: PSI 4500 ± 500
Elongation %: 700 ± 100
Application Temperature: 41°F - 122°F

Packaging

Rolls are provided in case quantities.
Rolls per case: 6
Palletization: 60 cases per pallet

Storage and Handling

Parablock Tape must be stored in a dry location out of direct exposure to the elements. Do not stack other materials on the tape.

1 year shelf life

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 10/2018