

PARASOLO™ WATERBLOCK SEALANT

Commercial Product Data Sheet



Parasolo Waterblock Sealant is a black, butyl-based high-viscosity sealant for use in conjunction with Siplast Parasolo series single-ply membrane systems. Parasolo Waterblock Sealant is designed for use in concealed applications such as sealing between Parasolo membranes and drain/penetration flashings.

Contact Siplast for specific approval on product uses.

PRODUCT INFORMATION

Total Solids by Weight:	>85%
Specific Gravity:	1.24 ± 0.1
Application Temp. (ambient and substrate):	32°F - 120°F (0°C – 48.9°C)
Shelf Life:	12 months (if unopened)

Application

Refer to the applicable Siplast Technical Guide for detailed information on application of Parasolo and Parasolo KEE membrane accessories. Clean-up with mineral spirits, toluene or xylene.

Do not use Parasolo Waterblock Sealant in conjunction with Siplast SBS Membrane Systems.



Storage and Handling

Store material in a clean and well-ventilated area at 50°F (10°C) – 90°F (32.2°C). Storage for extended periods outside this temperature range may shorten shelf life. Do not apply at temperatures of less than 32°F (0°C) or above 120°F (48.9°C). See product packaging and Safety Data Sheet (SDS) for specific information on the safe handling of this material.

Packaging

Primary Packaging: 10-oz cartridge (25 tubes per box)
Weight (box): 13 lbs (5.9 kg)