

TERAPRO VTS QUARTZ



Commercial Product Data Sheet

Product Description

Terapro VTS Quartz is a natural colored, high purity silica aggregate. Terapro VTS Quartz is washed, kiln-dried, and suitable for broadcast.

Product Uses

Terapro VTS Quartz is broadcast into the Terapro VTS Resin/Terapro VTS Quartz Filler mixture to achieve a skid-resistant surface.

Color

Terapro VTS Quartz is supplied in its natural light tan color.

Size

Terapro VTS Quartz silica size: 0.6 - 1.7 mm

Packaging

Terapro VTS Quartz is supplied in 50-lb (22.7 kg) paper bags.

Coverage Rate

Approximate consumption: 1 lb/sf (0.464 kg/sf) (5 kg/m²)

See recommendations for specific applications.

Application

Terapro VTS Quartz is broadcast into the Terapro VTS Resin/Terapro VTS Quartz Filler mixture before the resin/filler mixture sets. To properly broadcast Terapro VTS Quartz, the aggregate should be projected upward and allowed to fall down into the resin/filler mixture, rather than being projected into the resin at an angle. Broadcast to rejection, resulting in full and uniform coverage. After the resin/filler mixture is set, remove any loose Terapro VTS Quartz by sweeping, blowing with oil-free compressed air, or vacuuming and collecting/screening for later use.

Following the application of Terapro VTS Quartz, the VTS System is completed with a layer of catalyzed Pro Color Finish Resin.

Storage

Store in closed containers on a clean, flat surface. Bags should not be dropped. Store in a dry place, out of direct exposure to the elements.

Handling

Avoid generating dust. Consult the Safety Data Sheet (SDS) for additional information pertaining to this product.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 5/2015